



RAVE SYSTEMS RACKMOUNT Titan 2600S

Key Features Include:

- Tyan S2462UNG Motherboard with AMD-760MP Chipset
- One or Two AMD Athlon MP Processors
- Onboard Dual Ultra160 SCSI Controllers
- Onboard Dual ATA/100 IDE Controllers
- Onboard Dual 3COM 10/100Mb Ethernet
- Three 32-bit PCI Slots with Optional 64-bit
- Supports Windows 2003, 2000, XP, Solaris, and Linux (Kernal 2.4 or Later)
- Up to 3.5GB PC2100 DDR Memory
- 460 Watt Power Supply
- Two Year Warranty

Rave Systems Rackmount 2U 5 Bay Titan 2600S

The Rave Systems Rackmount 2U 5 Bay Titan 2600S provides flexibility, reliability, and power in a small form factor. Accelerated by one or two AMD Athlon MP processors and up to 3.5GB of RAM, the Rave Systems Titan 2600S delivers performance in a small 2U form factor. Our Rave Systems Titan 2600S features best-of-breed components from industry leading manufacturers. This combination delivers robust and reliable performance. Operating on Windows, Solaris, or Linux, the Rave Systems Titan 2600S provides an ideal solution for a vast array of heterogeneous computing applications.

Custom Built By Rave Computer

Tyan's S2462UNG motherboard includes the AMD-760MP chipset. This integration into Rave's 2U rackmount chassis provides a reliable cost-effective multi-processor solution. The Rave Systems Rackmount Titan 2600S provides steady performance with expanded connectivity. The robust motherboard includes 3COM dual 10/100Mb Ethernet ports, dual Ultra160 SCSI controllers, dual ATA/100 IDE controllers and three 32-bit PCI slots. The motherboard also features an ATI 8MB Rage-XL graphics accelerator, two PS/2 ports, two USB ports, and one serial port.

The rackmount chassis is an attractive 2U form factor steel enclosure with five 80mm fans to provide exceptional cooling capabilities. The chassis comes standard with a 460 watt power supply, four 3.5" low-profile front removable drive bays, an additional fixed 3.5" bay for a floppy drive and one 5.25" drive bay for removable media such as a CD-RW, DVD-ROM, CD-ROM, or a SCSI disk drive for additional storage.



ISO 9001:2000
Certified Company

Rave Computer Association, Inc.
1-800-966-7283

36960 Metro Court, Sterling Heights, MI 48312
Web site: www.rave.com
e-mail: info@rave.com

Rave Computer -- "Bringing Your Vision Into Reality!"

RAVE SYSTEMS RACKMOUNT TITAN 2600S



**RAVE COMPUTER
ASSOCIATION, INC.**
Headquarters
1-800-966-7283

Rave Financial Services
1-800-500-7283

e-mail
info@rave.com

SPECIFICATIONS

MOTHERBOARD	Tyan S2462UNG with AMD-760MP Chipset
PROCESSOR	One or Two AMD Athlon MP Processors
SYSTEM MEMORY	
Memory Type	PC2100 DDR, Error Checking and Correcting (ECC) (Four Slots)
Maximum Supported	3.5GB
EXPANSION SLOTS	
PCI	Three 32-bit Slots Optional 64-bit
ONBOARD GRAPHICS	ATI 8MB RageXL Graphics Accelerator
ONBOARD INTERFACES	
Network	Two 3COM 10/100Mb Ethernet Ports with Rearpanel RJ45 Connectors
SCSI	Two Ultra160 SCSI Controllers
IDE	Two ATA/100 IDE Controllers
Serial	One 9-pin Serial Port
Parallel	One Parallel Port
USB	Two USB Ports
PS/2	Two PS/2 Ports
FRONT ACCESSIBLE STORAGE	
	One 5.25" Bay for CD-RW, DVD, CD-ROM, or Removable Disk Drive Four 3.5" Bays for Removable Disk Drives One 3.5" Bay for 1.44MB Floppy Drive
SOFTWARE	
Operating System	Windows 2003, 2000, XP, Solaris, or Linux (Kernal 2.4 or Later)
CHASSIS	
Form Factor	2U
Physical Size	17"W x 3.5"H x 24"D
Weight	23.7 lb
Cooling Fans	Five 80mm
POWER SUPPLY	Single 460 Watt
ENVIRONMENT	
Minimum Operating Temp.	0° C (32° F)
Maximum Operating Temp.	55° C (131° F)

